

Grounding Ferrule - Shrouded Plain - 4/0 Copper

By Chance Lineman Tools & Equipment
Catalog # [C6002633](#)



Shrouded plain plug copper ferrule 4/0

Features

- GROUNDING FERRULE-PLAIN-SHROUDED- 4/0 CU
- Shrouded ferrules overlap onto the grounding cable jacket for stress relief to the terminal
- Two crimps secure the ferrule against the bare strands and one crimp applies on the jacket
- Available either factory-installed in pairs on any cable length specified or as separate individual units
- The ferrules install simply with a hydraulic crimping tool
- Complete illustrated installation instructions come with the ferrules and include a table for the crimping die sizes to use

General

Catalog Number	C6002633
Die Size - Section A	U166
Die Size - Section B	U-L
Material	Copper
Shrouded?	Shrouded
Terminal Connection Type	Pressure or Plain

UPC 096359233268

Dimensions

Weight 0.421 lb

Electrical Ratings

Current Rating	400 A
Fault Current - 15 Cycles	43000 A
Fault Current - 30 Cycles	30000 A

Conductor Related

Conductor Size 4/0 AWG

Product Assets

- [Catalogs - Grounding Equipment](#)
- [Sales Drawings - SA600-2630](#)
- [Specifications - C6002633](#)
- [Video - CHANCE Temporary Protective Grounding](#)