



27 kV, 150 kV BIL, Type C Standard
Porcelain Cutout w/100A 12kAIC
fuseholder

By Chance
Catalog # [C710313PB](#)

27 kV, 150 kV BL, Standard Type C Porcelain Cutout with a 100A, 12kAIC fuseholder, parallel-groove connector and a NEMA "B" crossarm bracket.



Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 - 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

Specifications

EU RoHS Indicator	No
-------------------	----

Configuration

Bracket Type	NEMA "B" Heavy Duty for crossarm
Corrosion Resistant?	No

Current

Fuselink Current Range	1A to 100A - removable buttonhead fuse link only
BIL	150 kV
Current Rating	100 A
Voltage - Radio Interference	Ambient @22kV
Creep and Leakage Distance	17.3" (440mm)
Reference Voltage Limit - Minimum	• No Restrictions thru 24.9kV • *26.4 thru 34.5kV
Voltage Rating	27 kV

Temperature Rise - Max. at 300A	35° C
Voltage - Maximum	27 kV

Dimensions

Length	19.750 in
Weight	25.666 lb.
Height	5.000 in
Width	13.250 in
Dimensions	19.750 in x 13.250 in x 5.000 in

General

Material type	Standard
UPC	096359030058
Type	Cutout
Description - Replacement	T710-313T
Fuse Holder	

Logistics

Pallet Quantity	42
Standard Package	1

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)



A Hubbell brand