



Safety switch, double throw, non fusible, 2 pole, 3 wire, 240VAC, 200A, Type 3R, bolt/hub prov, with neut

DTU224NRB

Product availability: Stock - Normally stocked in distribution facility

### Main

Product	Double Throw Safety Switch	
Duty Rating	General duty	
Disconnect Type	Non-fusible disconnect switch	
Factory Installed Neutral	Neutral (factory installed)	
Number of Poles	2	
Current Rating	200 A	
Voltage Rating	240 V AC	
Enclosure Rating	NEMA 3	
Motor power hp	15 hp at 240 V AC 50-60 Hz for 1 phase motors	

## Complementary

Short-circuit current	10 kA H or K	
Fuse type	H or K	
Mounting Type	Surface	
Wire Size	AWG 6300 kcmil copper or aluminium	
Tightening torque	340 lbf.in (38.4 N.m) (AWG 6300 kcmil)	
Depth	10.63 in (270.002 mm)	
Width	24 in (609.6 mm)	
Height	32.5 in (825.5 mm)	
Net Weight	65.98 lb(US) (29.93 kg)	

#### **Environment**

Certifications UL Listed

# Ordering and shipping details

Category	US10DE100133	
Discount Schedule	0DE1	
GTIN	785901174523	
Returnability	Yes	
Country of origin	MX	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# **Packing Units**

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	10.63 in (27.0 cm)	
Package 1 Width	23.23 in (59.0 cm)	
Package 1 Length	33.86 in (86.0 cm)	
Package weight(Lbs)	69.860 lb(US) (31.688 kg)	

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

## DTU224NRB

## **Technical Illustration**

## **Dimensions**



 TOP OF NEMA TYPE 3R DEVICES HAVE PROVISIONS FOR MAXIMUM 2:50(84) BOLT-ON HUB.