


CATALOG NUMBER CONDUCTOR RANGE SOL. HARDWARE BOLT APPROX. WT. STANDARD DIM C HEAD (HEX.) EACH LB. [KG] 7/8 [22.27] GC8002GL\* 1 3/8 [34.99] 11/4 [31.81] 9/16 [14.32] 5/16 [7.95] 16 [.07] #8 - #2 50 #8 - 1/0 1 1/2 [38.18] 13/8 [34.99] 1 [25.45] 9/16 [14.32] 5/16 [7.95] .24 [.11] GC8010GL\* GC8020GL\* #8 - 3/0 1 3/4 [44.54] 13/8 [34.99] 11/8 [28.63] 9/16 [14.32] 5/16 [7.95] .33 [.15] 25 #6 - 4/0 2 3/8 [60.44] | 11/2 [38.18] | 11/2 [38.18] 9/16 [14.32] 3/8 [9.54] GC8040GL\* .62 [.28] 50

ITEM DESCRIPTION MATERIAL MALE CASTING **BRONZE** FEMALE CASTING **BRONZE** SPACER BRONZE STAINLESS STEEL BOLT STAINLESS STEEL WASHER GROMMET NEOPRENE







## NOTES:

- 1. 1. ALL DIMENSIONS ARE FOR REFERENCE ONLY. DISTANCE IN. [MM], FORCE: LBS-Force [kN], TORQUE IN. LBS. [N.m], & WEIGHT LBS. [KG].
- 2. RATINGS:
- A. RECOMMENDED TORQUE: 5/16 HARDWARE 180 IN.LBS [20.34] 3/8 HARDWARE - 240 IN.LBS [27.12]
- 3. CERTIFICATIONS, SPECIFICATIONS & STANDARDS:
- A. \* RUS LISTED.
- B. ANSI C119.4 4. A SUFFIX IS ADDED TO THE CATALOG NUMBER TO DESIGNATE THE REQUIRED FITTINGS AS SHOWN IN THE TABULATION (EXAMPLE:GC8040GL):
  - "G" GROMMETS
  - "L" FACTORY INHIBITED AND BAGGED
  - "P" TIN PLATED CASTINGS

30822032798	08/22/23	ВМ	SI	AS	
EC#	DATE	CHANGED BY	CHECKED BY	APPROVED BY	
DESCRIPTION: WEIGHT, LBS					
FEMPLATE UPDATED SEE TABLE					<b>M</b> -1
ONE GROMMET REMOVED					\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
- -					CONFIDENTIAL: THIS DRAWING AND ITS ( CONFIDENTIAL AND THE PROPERTY OF HUBBELL P PUBLICATION, DISTRIBUT

CONTENTS ARE E EXCLUSIVE POWER SYSTEMS. NO JTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS

THIRD ANGLE

PROJECTION

\*HUBBELL POWER SYSTEMS, Inc.

PARALLEL CONNECTOR CU, GROOVE VISE, TYPE GC80XX.

CATALOG NUMBER: SEE TABLE

SIZE DWG NO. PART / ASSY NO. REV **SEE TABLE** CC-25843 DATE: 11/06/18 DRN BY: ADD SHEET 1 OF 1 SCALE: 2:1

WI-ENG-142 - 111020-R1

ADDITIONAL COMMENTS: -