


TYPE GCH4

COPPER CENTER BREAK SWITCH



Product Information

GCH4 Copper Center Break

The GCH4 is a two insulator, side opening outdoor air disconnect switch constructed primarily of copper. Operation is accomplished by the rotation of two insulators making the center break switch the easiest operating of all group operated switches. Proven by years of field experience, this switch takes full advantage of unique construction methods to provide both simple operation and long-term dependability. The GCH4 is commonly used in three-phase line or substation applications such as transformer or line disconnecting, breaker isolating, bypassing or bus sectionalizing. Operation of the GCH4 may be accomplished by either manual control or by motor operator.

Features

- *Testing.* The GCH4 has been tested to meet or exceed current IEEE standards. A test brochure outlining electrical and mechanical design tests conducted on the GCH4 is available upon request.
- *Jaw Contacts.* The GCH4 is supplied with line high pressure silver-to-silver jaw contacts producing the highest conductivity initially and over time. The contact fingers, fabricated from hard drawn copper, are silver plated and then electro-tin plated. The male contact, also of hard drawn copper, has a brazed silver overlay and then is electro-tin plated. The methods and materials used in the application of the silver provide surfaces of differing hardness with anti-galling properties, resulting in minimal wear over years of operation.
- *Bearings.* The GCH4 incorporates rugged switch bearings consisting of stainless-steel balls, stainless steel races, galvanized ductile iron bearing housing and rotors. Factory adjusted stops are provided with the bearing for ease of synchronization during installation.
- *Bases.* Hot dipped structural steel channel is used for the construction of the switch bases. Leveling studs are provided on the bearings for insulator alignment. Bases and base mounting dimensions can be customized to customer specifications and structure.
- *Hinge Contacts.* Transfer of the current at the hinge end of the blade is accomplished with a copper shunt that is formed and bolted in to place between the blades and terminal pad castings. The current transfer points of the shunt are silver plated before assembly. .

Accessories


- Grounding switch: Up to 164kA peak current
- Auxiliary Switches: Up to 16 contact decks are standard
- Outriggers: Custom designed for customer application
- Connectors: Can be added to customer switch order upon request

Load Break Devices

- Arcing Horn: Minimum standard on all switches
- Quick Break Whips
- TECORupters
 - Loop Split
 - Full Load



Configurations



- DIMENSIONS SHOWN IN INCHES - WEIGHT SHOWN IN POUNDS (INSULATORS INCLUDED)
- 8.3 - 72.5 kV 3" BOLT CIRCLE STATION POST INSULATORS
- 123 - 170 kV 5" BOLT CIRCLE STATION POST INSULATORS
- DIMENSIONS NOT FOR CONSTRUCTION PURPOSES
- CONTACT FACTORY FOR CERTIFIED PRINTS

CATALOG NO.	DIMENSIONS			STD MTG
	A	B	C	
GCH4-00812	24	20 9/16	19 5/8	8 1/4 X 24
GCH4-00820	24	21	25 1/2	8 1/4 X 24
GCH4-01512	24	23 1/16	19 5/8	8 1/4 X 24
GCH4-01520	24	23.5	28	8 1/4 X 24
GCH4-02712	24	27 1/16	19 5/8	8 1/4 X 24
GCH4-02720	24	27.5	32	8 1/4 X 24
GCH4-03812	24	31 13/16	19 5/8	8 1/4 X 24
GCH4-03820	24	31 1/2	36	8 1/4 X 24
GCH4-04812	30	35 7/16	21 3/8	8 1/4 X 30
GCH4-04820	30	35 7/8	40 3/8	8 1/4 X 30
GCH4-07212	42	43 1/2	29 6/8	8 1/4 X 42
GCH4-07220	42	43 15/16	31 1/4	8 1/4 X 42
GCH4-12312	60	61 15/16	35 3/8	8 1/4 X 60
GCH4-12320	60	64 1/16	*	8 1/4 X 60
GCH4-14512	72	67 7/16	43	8 1/4 X 72
GCH4-14520	72	74 1/16	*	8 1/4 X 72
GCH4-17012	84	77 1/2	47 3/4	8 1/4 X 84
GCH4-17020	84	82 1/16	*	8 1/4 X 84

* Refer to factory.



Numbering Sequence

GCH4	V	A	I	P	TR	LB	OP
	008	12	SIP	3	SEE CHART	AH	N
	015	20	SEP	5		QB	SH
	027		NA			LI	WG
	038		CS			N	MO
	048		INC			CS	P
	072						SH-P
	123						
	145						
	170						
							WG-P

Variant Configuration Key

V - Voltage (kV)	TR - Insulator TR
A - Current (A)	LB - Load Break Device
I - Insulator Ship Method	OP - Operator
P - Pivot Size (inches)	

Insulator Shipping Methods

- SIP** - SHIP IN PLACE
- SEP** - SHIPPED SEPARATE
- NA** - INSULATORS NOT INCLUDED
- CS** - CUSTOMER SUPPLIED
- INC** - WITH INSULATORS BULKED PACKED

Load Break Options

- AH** - ARCING HORN
- QB** - QUICK WHIPS
- N** - NONE
- CS** - CUSTOMER SUPPLIED
- LI** - TECORUPTERS
 - **FL** - FULL LOAD
 - **LS** - LOOP SPLIT

Operator Options

- N** - NONE SUPPLIED
- SH** - SWING HANDLE
- WG** - WORM GEAR
- MO** - MOTOR OPERATOR
- P** - MOTOR OP PROVISIONS
- SH-P** - MOTOR OP PROVISIONS SH
- WG-P** - MOTOR OP PROVISIONS WG

Example: GCH4-14512- SIP5288QBWG

VOLTAGE (kV)		INS TR
NOM	BIL	
8.3	95	202
15.5	110	205
27	150	208
38	200	210
48.3	250	214
72.5	350	216
123	550	286
145	650	288
170	750	291

CURRENT (A)			
CONT	PEAK	MOM	3 SEC
1200	99,000	61,000	38,000
2000	164,000	100,000	63,000









hubbelpowersystems.com

For product inquiries, please contact your local sales representative or customer service representative.

©2019 Hubbell Incorporated.
Because Hubbell has a policy of continuous product improvement,
we reserve the right to change design and specifications without notice.
Printed in the U.S.A. | TD_10_290_E