

Aluminum Automatic Dead End,
4/0 AAC, 4/0 AAAC, 4/0 ACSR
Conductor, SS Flex Bail.

By FARGO
Catalog # [GD409A](#)

Aluminum Automatic Dead End, 4/0 AAC, 4/0 AAAC, 4/0 ACSR
Conductor, Diameter range .505 - .595" (12.83 -15.11 mm), SS Flex
Bail.

Features


- Automatic Dead Ends for ACSR, AAC, and AAAC Conductor
- Galvanized steel stirrup clevis or Z-bail for primary applications and flexible or semi-flex bails for secondary applications
- Add "N" for neoprene covered Flex or Semi-flex bail
- Add "TA" for pulling eye (clevis bail only)

General

Bail Option	SS Flex Bail
Catalog Number	GD409A
Color Code	Pink
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Material - Bail	Stainless Steel
Material - Shell	High Strength Aluminum Alloy
Product Category	Flex Bail
Type	Automatic
UPC	096359308782

Dimensions

Weight	0.98 lb
--------	---------



*Representative Image

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;AAC-Oxlip-4/0-7
Conductor Diameter - Maximum	0.595
Conductor Diameter - Minimum	0.505
Conductor Diameter Range	0.505 - 0.595

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

Logistics

Pallet Quantity	1000
-----------------	------

Product Assets

[Catalogs - Distribution Connectors](#)
[Literature - Deadends For Overhead Connections](#)
[Literature - Ropes Course Industry Letter \(April 2021\)](#)
[Sales Drawings - CC-25241](#)
[Sales Drawings - GD-440A_Series_Overhead_Automatic_Deadend\(CC-25241\)](#)
[Specifications - GD409A](#)