

Automatic Splice, Full Tension, for 500, *556.5 AAC, 559.5 AAAC, 477 (18/1) ACSR

By FARGO
Catalog # [GLSF413](#)

Automatic Splice, Full Tension, for 500, *556.5 AAC, 559.5 AAAC, 477 (18/1) ACSR, Dia. Range .780 - .858 in



Features

- ANSI C119.4
- Class A connector
- Full tension (95% of conductor rated breaking strength unless noted otherwise)
- Innovative design to help reduce partial tension issues
- Indicators deploy upon full conductor insertion
- Jaws remain in place until conductor is fully inserted
- Simple, smooth installation

General

Color Code	White
Material	Aluminum Alloy
Trade Name	Fargo
UPC	096359610915

Dimensions

Length	24 in
Width	2.1 in

Conductor Related

Conductor Diameter - Maximum	0.858 in
Conductor Diameter - Minimum	0.78 in
Conductor Diameter Range	0.78 - 0.858
Conductor Type	<ul style="list-style-type: none">• AAC• AAAC• ACSR

Logistics

Pallet Quantity	240
-----------------	-----

Product Assets

[Catalogs - Distribution Connectors \(CA05127E\)](#)
[Installation Manuals - SureFit Full-Tension Aluminum Automatic Splices](#)
[Literature - SureFit Cross Reference \(TD05059E\)](#)
[Literature - Quick Reference Guide: Splices for Overhead Connections \(LEEDS-HPS-SPLICES-QUICK-REFERENCE-GUIDE-SF-EN-2023\)](#)
[Sales Drawings - Surefit Aluminum Automatic Splice \(CC-20854\)](#)
[Sales Drawings - Surefit Aluminum Automatic Splice \(CC-20854\)](#)
[Video - In Depth: SureFit Automatic Splice \(VI05121E0518\)](#)