



Ground Clamp - All Angle Mounted 6' II-B-5

by CHANCE Utility
Catalog ID: HG422965J

GROUND CLAMP - ALL ANGLE MTD 6FT -II-B-5, All-Angle.

Product Details

General

Bolt Installation Torque (Recommended)	33 ft-lbs
Handle Type	Hotstick
Jaw Type	Serrated Jaws
Material	Aluminum
Terminal Connection Type	Pressure
UPC	096359038788

Dimensions

Jaw Opening Size - Maximum	1.196 in
Jaw Opening Size - Minimum	.258 in
Length	6 in
Weight	5.145 lb

Electrical Ratings

Current Rating	400 A
Fault Current - 15 Cycles	43000 A
Fault Current - 30 Cycles	30000 A
Grounding Wire Capacity Maximum	4/0 Cable w/ Plain Terminal
Grounding Wire Capacity Minimum	#2 Cable w/ Plain Terminal

Certifications and Compliance

Fault Current - ASTM Grade	ASTM Grade 5
----------------------------	--------------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscshubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com