# **HUBBELL Power Systems**

## Hot Line Link, Y-Clevis Y-Clevis

By ANDERSON Catalog # HYYC3015

Hot line Y-Y-clevis eyes are used to connect associated hardware within an insulator string or connecting deadend clamps to yoke plates providing clearances for jumper ends. Shoulders are provided to accommodate hot line tools and bent bolts in the Y-clevises provide additional points of articulation within an assembly.

#### **Features**

- "Material: Body-Galvanized Ductile Iron, Bent bolt & Hex. Nut-Galvanized steel, Cotter pin-Stainless steel
- Shield nut can be supplied by adding suffix "SN" to catalog number"

#### General

Catalog Number	HYYC3015
Material	Ductile Iron
Material - Pin (Clevis)	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Cautaa	11)/\/C Carrian

Series HYYC Series
Strength Rating - Ultimate 30000 lb
Strength Rating - Ultimate 0 lb

Body

UPC 096359317715

#### **Dimensions**

Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Pin	0 in

Dimensions 15 in  $\times$  2.06 in  $\times$  0.75 in

Height 0.75 in Insulator Throat Diameter - 0 in

Maximum

Insulator Throat Diameter - 0 in

Minimum



\*Representative Image

Insulator Throat Diameter	0 - 0	
Range		
Length	15 in	
Length - Coupling	15 in	
Length - Pin	0 in	
Maximum Adjustment	0 in	
Ring Height	0 in	
Weight	6.493 lb	
Width	2.06 in	

#### **Conductor Related**

Conductor Diameter - 0 i	n	ı
--------------------------	---	---

Maximum

Conductor Spacing 0 in

#### **Certifications And Compliance**

Buy America(n)	Qualified	IAA	Compliant	(All	status	valio
----------------	-----------	-----	-----------	------	--------	-------

till December 2024)

### Logistics

Pallet Quantity 240

#### **Product Assets**

Catalogs - Transmission Connectors Catalog - Full Sales Drawings - HYYC-30-15 Specifications - HYYC3015

