

Jumper Terminals

Product Data and Conductor Size

Catalog Number	Conductor Range ⁽¹⁾			Pad Width	Length Inches (mm)	Die Size	Minimum Press Tons	Net Weight lb (kg)
	Outside Diameter Inches ⁽²⁾ Std Cond /	AAC Size Kcmil	ACSR Kcmil (Str)					
			ACSR/TW (Typ)					
	Compact/TW							
JTF07	0.595-0.679	300-350	266.8 (26/7) - 336.4 (18/1)	$\frac{1.7 (44)}{2}$	9.2 (234)	07CD	12	0.4 (.19)
	0.547-0.611							
JTF08	0.680-0.765	397.5-400	336.4 (18/1) - 397.5 (20/7)	$\frac{1.7 (44)}{2}$	9.8 (249)	08CD	12	0.6 (.27)
	0.630-0.695		336.4 (T23)					
JTF09	0.766-0.855	450-550	397.5 (24/7) - 477 (24/7)	$\frac{2.2 (56)}{2}$	10.4 (264)	09CD	12	0.8 (.36)
	0.702-0.776		397.5 (T13) - 477 (T13)					
JTF10	0.856-0.950	556.5-650	477 (26/7) - 636 (18/1)	$\frac{2.2 (56)}{2}$	11.4 (290)	10CD	60	1.1 (.49)
	0.789-0.858		477 (T16) - 565.3 (T16)					
JTF11	0.950-1.045	700-795	636 (18/1) - 795 (36/1)	$\frac{3.0 (76)}{4}$	12.1 (307)	11CD	60	1.5 (.68)
	0.880-0.930		636 (T13) - 664.6 (T13)					
JTF12	1.026-1.131	795-954	795 (36/1) - 900 (45/7)	$\frac{3.0 (76)}{4}$	12.7 (323)	12CD	60	1.8 (.81)
	0.960-1.010		795 (T7) - 795 (T16)					
JTF13	1.140-1.235	1000-1113	795 (30/19) - 1033.5 (45/7)	$\frac{3.0 (76)}{4}$	13.4 (340)	13CD	60	2.2 (.99)
	1.046-1.108		795 (T23) - 959.5 (T16)					
JTF14	1.236-1.330	1192.5-1300	954 (30/19) - 1272 (36/1)	$\frac{3.0 (76)}{4}$	14.0 (356)	14CD	60	2.7 (1.2)
	1.125-1.196		1035 (T13) - 1158.4 (T13)					
JTF15	1.331-1.425	1351.5-1510.5	1192.5 (54/19) - 1351.5 (54/19)	$\frac{3.0 (76)}{4}$	14.6 (371)	15CD	60	3.1 (1.4)
	1.212-1.300		1192.5 (T13) - 1351.5 (T13)					
JTF16	1.426-1.520	1590-1700	1431 (45/7) - 1590 (45/7)	$\frac{3.0 (76)}{4}$	15.9 (404)	16CD	60	3.9 (1.7)
	1.290-1.382		1431 (T7) - 1590 (T7)					
JTF17	1.521-1.615	1750-1900	1590 (54/19) - 1868 (68/7)	$\frac{4.0 (102)}{4}$	16.5 (419)	17CD	60	4.7 (2.1)
	1.385-1.504		1590 (T13) - 1949.6 (T7)					
JTF19	1.630-1.805	2000-2300	2034.5 (72/7) - 2312 (76/19)	$\frac{4.0 (102)}{4}$	17.8 (452)	19CD	100	6.1 (2.8)
	1.504-1.608		1949.6 (T7) - 2156 (T8)					
JTF20	1.806-1.900	2500	2515 (76/19)	$\frac{4.0 (102)}{4}$	18.4 (467)	20CD	100	7.1 (3.2)
	1.662-1.710							

NOTE: Conventional (AH Die) jumper terminals in catalog number series 33XXX listed separately. To specify stainless steel hardware add "SS" to catalog number. Example: JTF09SS

(1) Compact AAC and ACSR/TW conductor terminal diameter ranges are the lower of the dual listings.

(2) These terminals also approved for minimum tension applications on AAAC and ACAR conductors within the diameter ranges.