



# General Use - Parallel Bronze With Separator

BRONZE
KR

For copper to copper conductor connections.

- Material:** **Body** - High Strength Bronze Alloy  
**Separator** - Copper Alloy  
**Retaining Ring** - Neoprene Rubber  
**Hardware** - Silicon Bronze
- Options:** "TP" suffix - Tin plated



## Product Data & Conductor Size

CATALOG NUMBER	CONDUCTOR RANGE AWG (IN.) [MM]		HARDWARE		WIDTH IN. (MM)	DEPTH IN. (MM)	HEIGHT IN. (MM)	STANDARD PACK	
	MAIN	TAP	BOLT SIZE	WRENCH SIZE				QTY	CARTON WEIGHT LBS. (KG)
	CU	CU							
KR1	#4 STR. - 1/0 STR. (0.232 - 0.373) [5.89 - 9.47]	#8 SOL. - 1/0 STR. (0.128 - 0.373) [3.25 - 9.47]	5/16	1/2	1.313 (33.34)	.938 (23.81)	1.500 (38.10)	25	4.500 (2.04)
KR2	#3 STR. - 2/0 STR. (0.229 - 0.419) [5.83 - 10.64]	#6 SOL. - 2/0 STR. MCM (0.162 - 0.419) [4.11 - 10.64]	3/8	9/16	1.625 (41.28)	1.063 (26.99)	1.781 (45.24)	25	8.750 (3.97)
KR3	#1 STR. - 4/0 STR. (0.328 - 0.528) [8.33 - 13.41]	#6 SOL. - 4/0 STR. MCM (0.162 - 0.528) [4.11 - 13.41]	3/8	9/16	1.750 (44.45)	1.125 (28.58)	2.125 (53.98)	25	10.750 (4.88)
KR4	2/0 STR. - 350 MCM (0.414 - 0.681) [10.52 - 17.30]	#4 SOL. - 350 MCM (0.204 - 0.681) [5.18 - 17.30]	1/2	3/4	2.125 (53.98)	1.375 (34.93)	2.563 (65.09)	10	7.800 (3.54)
KR5	3/0 STR. - 500 MCM (0.464 - 0.813) [11.79 - 20.65]	#4 SOL. - 500 MCM (0.204 - 0.813) [5.18 - 20.65]	1/2	3/4	2.250 (57.15)	1.500 (38.10)	2.938 (74.61)	10	8.600 (3.90)
KR6	350 - 800 MCM (0.679 - 1.031) [17.25 - 26.19]	#2 STR. - 800 MCM (0.292 - 1.031) [7.42 - 26.19]	1/2	3/4	2.500 (63.50)	1.625 (41.28)	3.438 (87.31)	10	12.500 (5.67)
KR7	450 - 1000 MCM (0.772 - 1.152) [19.61 - 29.26]	1/0 STR. - 1000 MCM (0.368 - 1.152) [9.35 - 29.26]	5/8	15/16	3.000 (76.70)	2.000 (50.80)	4.000 (101.60)	5	12.450 (5.65)

DD-17