

## KVSW28, Mechanical Connector with Spacer Bar

By Burndy  
Catalog # [KVSW28](#)

Mechanical Connector For CUWeld and Copper Supplied with a CU alloy Spacer that separates run and tap conductors, Run: 1/0 str. - 4/0 str., Tap: 6 sol. - 4/0 str.



### Features

- Compact, 2-piece, high strength, high copper alloy, recommended for heavy duty connections
- High copper alloy spacer bar separates run and tap conductors
- Provides high contact pressure, confines conductor strands and assures vibration-proof connection
- Longer peened bolt permits swivel action for easier installation
- Neoprene rings hold silicon bronze bolts in place during installation
- Installed with ordinary wrench

### Application

For Copper And Copperweld Conductors

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - Copper Solid Tap Range	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> </ul>
Conductor - Copper Solid Tap Range	6 AWG-4/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> <li>• 1/0</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> </ul>

Conductor - Copper Str Run Range 1/0 str. - 4/0 str.

Conductor - Copper Str Tap

- 6 AWG
- 5 AWG
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG

Conductor - Copper Str Tap Range 6 sol. - 4/0 str.

Conductor Type CU C Str-Size

### Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - Height inch	2.50 in
Package Height	0.000 in
Dimension - Height mm	63.50 mm
Dimension - Stud Size inch	3/8 in
Dimension - Width inch	1.67 in
Dimension - Length Overall inch	1.04 in

### Force Related

Installation Torque Recommended in-lb 240 LBS/in

### General

Trade Name	OKLIP™
Sub Brand	OKLIP
Plated	N
Type	KVSW
UPC 12 Digit	781810066553
UPC 14 Digit GTIN	00781810066553
Material	Copper
Plating Type	Unplated
UPC	781810066553

### Logistics

Minimum Pack Quantity 1

Carton Quantity 25  
Pallet Quantity 3375

## Product Assets

[Catalog \[English\]](#)

---



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved  
BRDY-KVSW28-SPEC-EN | REV 4/2026