



25 kV, 600 A, Single Insulator Disconnect

By Chance
Catalog # [M3C256B](#)

SWITCH, M3C 25 kV 125BIL 600A

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125 and 150kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Uses Chance Type C Polymer Cutout Insulator Assemblies
- Uses NEMA B Brackets for Cross Arm mounting
- Load Break Option Available

General

Catalog Number	M3C256B
UPC	096359391142

Dimensions

Dimensions	24.500 in x 13.500 in x 6.000 in
Height	6 in
Length	24.5 in



Weight	13.65 lb
Width	13.5 in

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

Logistics

Pallet Quantity	24
-----------------	----

Product Assets

- [Catalogs - Hookstick Operated Switches](#)
- [Installation Manuals - Type M3C Single Insulator Disconnect Switch for Distribution Switching](#)
- [Literature - HPS/CHANCE® M3C Disconnect](#)
- [Sales Drawings - SA-M3C25](#)
- [Specifications - M3C256B](#)



A Hubbell brand