

Specs

Documents

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Ports Tap	1

Dimensions

Drive Size Main	1-1/16
Drive Size Tap	5/8
Drive Type Main	Eyebolt
Drive Type Tap	Hex
Height (IN)	5.573
Height BX (IN)	6
Height (mm)	141.5542
Length (IN)	3.505
Length (mm)	89.027
Weight (LB)	0.416587501108482
Weight BX (LB)	10
Width (IN)	0.9
Width BX (IN)	10.75
Width (mm)	22.86

Additional Technical Specifications

Conductor Type	Stranded
Conductor Type	Solid

Bolt and Screw Sizes

Wire Binding Screw Size	7/16-14
Wire Binding Screw Size	9/16-18

Material and Finish

Conductor Material	Aluminum
Conductor Material	Copper
Connector Finish	Clear
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Anodized
Wire Binding Hardware Material	Aluminum

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	1/0 Sol - 6 Sol
Conductor Range AL Stranded (Primary, run, main, line)	600 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	1/0 Sol - 6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	600 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Color

Color	Silver
Color	Copper

Testing Standards

ANSI Specification	ANSI C119.4 Class A
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	67656677686