

Quadri*Sil Horizontal Line Post Insulator

By Ohio Brass
Catalog # [P250029S1020](#)



2.5" Line Post, Standard Leak, Horizontal Clamp top, Aluminum Gain Base with 12" CL holes for 7/8" bolts

Features

- Made from hydrophobic silicone polymer

Specifications

EU RoHS Indicator Contact Manufacturer

Configuration

Number of Sheds 24

Current

Arc Distance - Dry	29.8 IN (756 MM)
Flashover Voltage - 60 Hz Wet	275
Flashover Voltage - 60 Hz Dry	305
Creep and Leakage Distance	76 IN (1930 MM)
Critical Impulse Flashover (CIFO) - Positive	465
Critical Impulse Flashover (CIFO) - Negative	580
kV Class	115.00 kV

Dimensions

Length - Effective	42.4 in
Angle	12
Thickness - Housing	> 3MM
Diameter - Shed(s)	5.06
Width	8.06 in
Rod Diameter	2.5 in
Length	14 in

Force Related

Cantilever Bending Strength - Routine	2275 LB
Cantilever Bending Strength - Max.	4550 LB

General

Fitting - Ground End	Aluminum Gain
UPC	096359442004
Shed Style	Uniform
Fitting - Live Line End	Horizontal Clamp top

Product Assets

[Catalog \[English\]](#)