

## ABS Pole Covers

### 36.6kV Covered-Phase-to-Covered-Phase



### Features & Applications

- Tested to ASTM F712 Class 4
- Protection from accidental brush contact with energized components during pole removal/ installation and other line maintenance
- Made of ABS Plastic
- Covers can be joined by overlapping impressions.


Catalog No.	Overall Length	Weight
<b>9" (22.9 cm) Diameter Pole Covers</b>		
PSC4060699	72" (182.9 cm) long	13 lb. / 5.9 kg.
PSC4060700	48" (121.9 cm) long	11 lb. / 5.0 kg.
PSC4060701	36" (91.4 cm) long	9 lb. / 4.1 kg.
PSC4060702	24" (61.0 cm) long	6 lb. / 2.7 kg.
PSC4060703	12" (30.5 cm) long	4 lb. / 1.8 kg.
<b>12" (30.5 cm) Diameter Pole Covers</b>		
PSC4060704	72" (182.9 cm) long	19 lb. / 8.6 kg.
PSC4060705	48" (121.9 cm) long	13 lb. / 5.9 kg.
PSC4060706	24" (61.0 cm) long	7 lb. / 3.2 kg.
PSC4060707	12" (30.5 cm) long	4 lb. / 1.8 kg.

## Flexible Stinger and Crossarm Covers

### Features & Applications

- Made from Orange, Type II rubber (ozone resistant)
- Crossarm cover rated Class 2 (17kV Phase-to-Phase)
  - Maximum arm size of 4" (102mm) x 4.5" (114mm)
  - Meet or exceed ASTM D1049
  - Provides insulation to support conductors in linehose during energized maintenance
- Stinger Covers rated Class 2 (17kV Phase-to-Phase) and Class 3 (26.5kV Phase-to-Phase)
  - Meet or exceed ASTM D1050
  - Maximum conductor diameter of 1.1" (28mm)
  - Provides the flexibility needed to use on stingers in addition to overhead lines

Catalog No.	Description	Weight
PSC4060672	Class 2 Type II Rubber Insulating Crossarm Cover	3.1 lb. / 1.4 kg.
PSC4060674	Class 2 Type II Rubber Stinger Cover 35.0" (888 mm)	3.0 lb. / 1.4 kg.
PSC4060675	Class 2 Type II Rubber Stinger Cover 15.8" (400 mm)	1.2 lb. / 0.5 kg.
PSC4060748	Class 3 Type II Rubber Stinger Cover 36.0" (914mm)	5.0 lb. / 2.3kg.



PSC4060672



PSC4060675

PSC4060674



PSC4060748