

## Rubber Insulating Blankets

### Features & Applications

- Meet ASTM Standard Specification D1048
- Type II (ozone-resistant)
- Class 4 blankets maximum use voltage 36kV and proof tested at 40kV AC
- Class 2 blankets maximum use voltage 17kV and proof tested at 20kV AC

### Performance-Designed Material

- Protect workers from accidental contact with energized components during line maintenance
- Made of ozone/corona-resistant elastomer
- Offer excellent performance properties with ASTM Standard Specification D1048
- Special formulation exhibits superior resistance to long-term aging/checking
- Will retain its high-visibility orange color

### Versatile Protection, Maximum Rating

- Flexible to cover many irregular shapes
- Used with conductor covers (flexible or rigid) on deadends, apparatus, secondary racks, poletop pins and crossarms
- Blankets may be used in applications which require lower Class or type
- Designed with perimeter eyelets to accept CHANCE button C4060532 and most other buttons existing in the field
- 1.5"-diameter center hole on slotted blankets will easily fit around common hardware



Cat. No. C4060532



### Solid Blankets

Catalog No.	Description	Weight
PSC13	Class 4 22" x 22", 28 eyelets	2.7 lb. / 1.2 kg.
C4060346	Class 4 36" x 36", 6 eyelets	8¼ lb. / 3.7 kg.




### Slotted Blankets

Catalog No.	Description	Weight
C4060348	Class 4 36" x 36", 28 eyelets	8¼ lb. / 3.7 kg.
PSC4060708	Class 2 22" x 22", 12 eyelets	3 lb. / 1.4 kg.
PSC4060724	Class 4 22"x22", 28 eyelets	3.2 lb. / 1.5 kg.

### Accessories

Catalog No.	Description	Weight
C4060530	Clamp Pin, Rubber Glove	0.27 lb. / 0.12 kg.
C4060531	Clamp Pin, Hot Stick	0.37 lb. / 0.17 kg.
PSC4060676	In-line Clamp Pin, Hot Stick	0.7 lb. / 0.3 kg.
C4060532	Button, Rubber Blanket	⅛ lb. / 0.1 kg.
PSC4060759	Magnetic Blanket Button	2.4oz / 0.07kg.
PSC4060760	Back-To-Back Blanket Button	0.8oz / 0.02kg.
C4032998	Storage Cannister*, no handle	6 lb. / 2.7 kg.
C4032999	Storage Cannister* w/ handle	7⅞ lb. / 3.5 kg.

\*For details, see Catalog Section 2500.



Hot Stick Clamp  
Catalog No. C4060531  
Eyes and special handle shape for easy placement by clampstick



Rubber Glove Clamp  
Cat. No. C4060530  
Special handle shape also fits clampstick for easy placement



Hot Stick Clamp  
Catalog No. PSC4060676  
For in-line use in grip-all clampstick



Blanket Buttons  
Cat. No. C4060759/  
C4060760  
For use with CHANCE rubber insulating brackets

