

BOLT, SHOULDER EYE, 3/4in x 10in

By Chance Catalog # PSSE3410CW

Shoulder eye bolts are used to support suspension insulators in deadend applications. The flat base of the eye functions as a washer to protect structure of the wood member.

Features

- 6" thread length
- Includes one square nut and cone pointed end
- Rated tensile strength is 22,000 lbs.
- Galvanized per CSA G164-M
- Manufactured in compliance with Canadian CSA C83-96 specification and Charpy level 1 impact properties with average minimum energy absorption of 20 joules when tested at -20 degrees C per ASTM A370

General

| Catalog Number | PSSE3410CW |
|------------------|------------------------|
| Coating | Galvanized, CSA G164-M |
| Material | Steel |
| Tensile Strength | 22000 lb. |
| UPC | 096359600435 |

Dimensions

| Diameter | 0.75 in |
|------------------------|---------|
| Diameter (Fraction) | 3/4 in |
| Distance From Pole | N/A |
| Length | 10 in |
| Length - Threaded Area | 6 in |
| Weight | 0 lb |
| | |

Certifications And Compliance

Industry Standard(s)

Logistics

Pallet Quantity 720

Product Assets

Catalogs - Fasteners - Canadian Standard (CSA) Sales Drawings - Shoulder Eye Bolts, 3/4 (CW) Specifications - PSSE3410CW



CSA C83.67