



BOLT, SHOULDER EYE, 3/4in x 12in

By Chance
Catalog # [PSSE3412CW](#)



Shoulder eye bolts are used to support suspension insulators in deadend applications. The flat base of the eye functions as a washer to protect structure of the wood member.

Features

- 6" thread length
- Includes one square nut and cone pointed end
- Rated tensile strength is 22,000 lbs.
- Galvanized per CSA G164-M
- Manufactured in compliance with Canadian CSA C83-96 specification and Charpy level 1 impact properties with average minimum energy absorption of 20 joules when tested at -20 degrees C per ASTM A370

General

Catalog Number	PSSE3412CW
Coating	Galvanized, CSA G164-M
Material	Steel
Tensile Strength	22000 lb.
UPC	096359573395

Dimensions

Diameter	0.75 in
----------	---------

Diameter (Fraction)	3/4 in
Dimensions	16.000 in x 3.000 in x 1.500 in
Distance From Pole	N/A
Height	1.5 in
Length	16 in
Length - Threaded Area	6 in
Weight	2.3 lb
Width	3 in

Certifications And Compliance

Industry Standard(s)	CSA C83.67
----------------------	------------

Logistics

Carton Quantity	15
Pallet Quantity	720

Product Assets

[Catalogs - Fasteners - Canadian Standard \(CSA\)](#)
[Sales Drawings - Shoulder Eye Bolts, 3/4 \(CW\)](#)
[Specifications - PSSE3412CW](#)



A Hubbell brand