



SKU: PTF4-750CJUP

UPC: 0676566785950

Features & Benefits:

Description: Clear Insulated Aluminum Slip Fit Padmount Transformer Lug, Dual Rated, Conductor Range 750-1/0, 1-14 Stud Size, 4 Ports, With De-Ox

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	4
Number of Ports Tap	0

Dimensions

Drive Size Main	5/16
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	NA
Height (IN)	0
Height BX (IN)	17
Length (IN)	0
Weight (LB)	0
Weight BX (LB)	13.38
Width (IN)	0
Width BX (IN)	11.125

Additional Technical Specifications

Conductor Type	Stranded
Dielectric Strength	240 V/Mil
End Hole Style	Slip-fit

Material and Finish

Conductor Material	Aluminum
Connector Finish	Clear
Insulation	Plastisol
Locking Screw Finish	Tin
Locking Screw Material	Aluminum
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6

Direct Burial	No
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	67656678595

Environment and Temperature

Water tight	No
-------------	----

Testing Standards

ANSI Specification	ANSI C119.4 Class A
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Bolt and Screw Sizes

Locking Screw Drive Size	5/16
Locking Screw Drive Type	Internal Hex
Transformer Stud Size	1-14
Wire Binding Screw Size	15/16-16

Color

Color	Clear
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Street Light Tap	No
Wire Combinations	NA