



SKU: PTF6-350JSLP

UPC: 0676566784038

Features & Benefits:

**Description:** Aluminum Slip Fit Padmount Transformer Lug, Dual Rated, Conductor Range 350-10, Street Light Range 2-14, 5/8-11 Stud Size, 6

Ports, With De-Ox

# **Specs**

Additional Class Attributes	
Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	7
Number of Ports Tap	1

Additional Technical Specificat	tions
Conductor Type	Stranded
End Hole Style	Slip-fit

Dimensions	
Drive Size Main	5/16
Drive Size Tap	5/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	1.25
Height BX (IN)	6
Height (mm)	31.75
Length (IN)	8.92
Length (mm)	226.568
Weight (LB)	0.845312114817678
Weight BX (LB)	23.6
Width (IN)	1
Width BX (IN)	10.75
Width (mm)	25.4

Material and Finish	
Conductor Material	Copper
Connector Finish	Clear
Insulation	NA
Locking Screw Finish	Tin
Locking Screw Material	Aluminum
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### General



**Baq Quantity** 

**Carton Quantity Description** STD PACK QTY 24

**Direct Burial** No Yes **Dual Rated NEMA Code** S-569-1 67656678403 **UPC Code** 

### **Environment and Temperature**

Water tight No

#### **Testing Standards**

**ANSI Specification** ANSI C119.4 Class A

**Prop65 Compliance** This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

**UL Control Number** NA

**UL File Number** NA

## **Bolt and Screw Sizes**

**Locking Screw Drive Size** 5/16 **Locking Screw Drive Type** Internal Hex **Transformer Stud Size** 5/8-11 Wire Binding Screw Size 5/8-18

#### Color

Color Silver

## **Conductor Ranges**

Conductor Range AL Solid (Secondary, tap, load) NA Conductor Range AL Stranded (Primary, run, main, line) 350 kcmil - 10 Str Conductor Range AL Stranded (Secondary, tap, load) 2 Str - 14 Str Conductor Range CU Solid (Primary, run, main, line) NA Conductor Range CU Solid (Secondary, tap, load) NA

Conductor Range CU Stranded (Primary, run, main, line) 350 kcmil - 10 Str Conductor Range CU Stranded (Secondary, tap, load) 2 Str - 14 Str

NA Conductor Range AL Solid (Primary, run, main, line) Street Light Tap Yes