

Utility - Three Phase Transformer Connectors for Underground Use

PTLH - Heavy Duty Transformer Lugs

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 class A specifications
- * Range taking design reduces inventory
- * Rated for 600 volts
- * Mounting holes at standard NEMA 1.75" spacing



PTLH500-64P
SHOWN

Catalog Number	Mounting Holes	Number of Ports	Dimensions, Inches			Wire Range KCMIL
			W	H	L	
PTLH600-86P	8	6	7.63	1.50	5.50	600 - #6
PTLH600-128P	12	8	10.13			
PTLH750-P	2	1	1.44	1.81	6.19	750 - 1/0
PTLH750-42P	4	2	2.75			
PTLH750-43P	4	3	4.06			
PTLH750-64P	6	4	5.37			
PTLH750-84P	8	4	6.25			
PTLH750-106P	10	6	8.00			
PTLH750-128P	12	8	10.40			
PTLH1000-P	2	1	1.63	1.81	6.19	1000 - 1/0
PTLH1000-42P	4	2	3.25			
PTLH1000-43P	4	3	4.75			
PTLH1000-84P	8	4	6.25			
PTLH1000-126P	12	6	9.88			
PTLH1000-148P	14	8	12.25			

OPTIONS:

A - Anodized set screws

T - Tin Plated

For omission of oxide inhibitor delete suffix "P"

Covers available

Example:

PTLH500-64AP

Anodized Screws

Inhibitor (must be last)