



Mini circuit breaker, QO, 100A, 2 pole, 120/240VAC, 10kA, plug in

QO2100

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker	
Range	QO	
Current Rating	100 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Plug-in	
Number of Poles	2P	
Circuit Breaker Type	Standard	
Ratings	HACR rated	
Electrical Connection	Box lugs	

Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 4AWG 2/0 copper or aluminium	
Tightening Torque	49.6 lbf.in (5.6 N.m)	
Height	3.5 in (89 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.507 lb(US) (0.230 kg)	

Environment

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	US1DE2A00104	
Discount Schedule	DE2A	
GTIN	785901501305	
Returnability	Yes	
Country of origin	MX	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	3.30 in (8.38 cm)	
Package 1 Width	1.60 in (4.06 cm)	
Package 1 Length	3.80 in (9.65 cm)	
Package weight(Lbs)	11.36 oz (322.06 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	51	
Package 2 Height	4.400 in (11.176 cm)	
Package 2 Width	14.00 in (35.56 cm)	
Package 2 Length	20.900 in (53.086 cm)	
Package 2 Weight	36.84 lb(US) (16.71 kg)	
Unit Type of Package 3	PAL	
Number of Units in Package 3	2142	
Package 3 Height	32.00 in (81.28 cm)	
Package 3 Width	42.00 in (106.68 cm)	
Package 3 Length	42.00 in (106.68 cm)	
Package 3 Weight	1566.000 lb(US) (710.325 kg)	

Contractual warranty

Warranty (in months)

40



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	19	

Use Better


Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



Product data sheet

QO2100

Image of product / Alternate images

Alternative

Technical Benefits Thermal Magnetic Breaker



Miniature circuit breaker rated at 100A





Product characteristics conformity is certified by the Underwriters Laboratories (UL)





The current capacity that this circuit breaker is able to interrupt before breaking is 10kA



Quickly identify tripped breakers with our Visi-Trip indicator



Compatible with QO electrical panels and CSEDs with 2 spaces









Qwik-Open" technology - Overload and Short circuit protection



Market-leading circuit protection



