

CHART 1


HPS NO.	1	2	3	APPLICATION RANGE
	APPLIED LENGTH	NECK SIZE	CONDUCTOR COLOR CODE	
QWSP4372	19	1.77	ORANGE	.245 TO .277 (6.22 TO 7.04 mm)
QWSP4372NT				
QWSP4374	24	1.77	RED	.316 TO .357 (8.03 TO 9.07 mm)
QWSP4374NT				
QWSP4375	26	1.77	YELLOW	.358 TO .405 (9.09 TO 10.29 mm)
QWSP4375NT				
QWSP4376	28	1.77	BLUE	.406 TO .459 (10.31 TO 11.66 mm)
QWSP4376NT				
QWSP4377	31	1.77	ORANGE	0.460 TO 0.520 (11.68 TO 13.21 mm)
QWSP4377NT				
QWSP4378	32	1.77	RED	.521 TO .588 (13.23 TO 14.94 mm)
QWSP4378NT				
QWSP4379	23	1.77	PURPLE	0.589 TO 0.665 (14.96 TO 16.89 mm)
QWSP4379NT				
QWSP4380	25	1.77	BROWN	0.666 TO 0.755 (16.92 TO 19.18 mm)
QWSP4380NT				
QWSP4381	32	1.77	RED	0.756 TO 0.858 (19.20 TO 21.79 mm)
QWSP4381NT				

NOTES:

- ALUMINUM CLAD STEEL.
- DIMENSIONS: INCHES (MILLIMETERS) FOR REFERENCE ONLY.
- HAND LAY STANDARD DIRECTION: RIGHT.
- SPOOL INSULATORS SHOULD BE PER ANSI 53-1, 53-2, 53-3 (1-3/4" NECK DIA).
- SUFFIX "NT" MEANS NO TIE TUBE.
- CLASSIFICATION OF DIMENSIONS AND REQUIREMENTS FOR INSPECTION:

CRITICAL ---  MAJOR ---  MINOR --- 

INSPECTION SYMBOL DRAWING
 SYMBOLS USED: 1-3
 SYMBOLS NOT USED: NONE

42422	09/30/2011	KBG	KBG	DELMAR	 HUBBELL POWER SYSTEMS
EC #	DATE	CHG BY	RESP ENG		
DESC OF DWG: --ADDED NEW SKU'S -- -- --				CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	TITLE QUIK-WRAP™ SPOOL TIE
REASON(S) FOR CHANGE: -- DISPOSITION OF MATERIAL: --					SIZE DWG NO. CAT / PART / ASSY NO. REV C CC-19594 SEE CHART 01
				DO NOT SCALE THIS DRAWING	DRN BY TVD DATE 3/24/10 SHEET 1 OF 1