



**Alternate Catalog No. RRK 6**  
**Catalog No. RRK6**

**Description: AL Comp Splice kit No6 Flood Seal**

**UPC No 783786746347**

**Home > Medium Voltage Utility Solutions > Homac > Wire or cable compression splice**

Aluminum Flood Seal Compression Splice Kit, Radiating Rib Splice kit, #6 Stranded - Compressed - Compact. Installing Dies UT 3, 1/2, TQ, 42, 163, 1/2. Strip Length 1 inch. Splice Length 2 inch, Largest Outside Diameter 37/64 inch. Includes Flood Seal Insulating Cover. For Aluminum Conductors Only.

**Descriptors**

Category	Wire or cable compression splice
Special Features	Prefilled with Oxide Inhibitor to Prevent Oxidation and Keep Out Moisture. Rubber Flood-Seal Insulating Cover fits snugly for maximum heat dissipation, no tape required. Compact size. Radiating rib design dissipates heat, centers the watertight insulating cover and seals perfectly every time.
Application	Dissipate heat and make perfect watertight seals.

**Specifications**

Connection	Compression
Conductor Range	#6 AWG
Number Of Conductors	2
Material	Aluminum Connector, EPDM Cover
Color	Blue
Insulation	yes

**Classifications**

Brand Name	Homac
Standard	ANSI C119.4

**Dimensions**

Size	2 inch Connector, 4-1/8 inch Cover
------	------------------------------------

**Compliance and Certifications**

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant