



## Account Details

Account No.	9036149_USS6_10_10
Account	KENTUCKY ASSOC OF ELEC COOPS
Address	KENTUCKY ASSOC OF ELEC COOPS, 4300 CHAMPIONS TRACE LN, , LOUISVILLE, Kentucky, 40218, United States
Sales Org.	ABB Installation Products USA
Sales	Distribution
Currency	USD
As on Date	09-09-2024

Catalog No. SA400NTN

## Product Details

UPC: 783786750207



Details: Tin-Plated Aluminum Two-Hole Lug. Wire Range 400 Compressed, 336.4 - 400 Stranded, 500 Compact AL-CU, 366.4 (18/1) - 397.5 (18/1) ACSR. Installing dies 96, 299, 655, 321, 316, 13A, 1 1/8-1, 472, CSA28. Length 6-3/8 inch. Pad 1-1/4 inch wide x 3 inch long x 25/64 inch thick. (2) 9/16 inch diameter holes on 1-3/4 inch center. Barrel 2-7/16 inch. Oxide Inhibitor. Green Cap.

## Product Details

### Details

Catalog No.	SA400NTN	UPC	783786750207
Description	AL 2 Hole Lug 400 Tinplated	GSA Compliance	No
Std. Package Weight	0.390 LB	Discount Schedule	92
Product Family	92B	CCC	
Restock Fee		Currency	USD
Customer Reference No.		Notes	
Brand Name	HOMAC	Package Qty.	1
Minimum Order Qty.	175	Country of Origin	United States


## Specifications

### General Characteristics

Category	Wire connectors
Type	Compression Lug Two Hole
Special Features	Dual-Rated for use with Aluminum and Copper Conductors. Made from Aluminum for High Strength and High Conductivity. Connector Bores coated with Oxide Inhibitor to Prevent Oxidation. Marked with conductor sizes and die references.
Application	Designed for General Applications and for Installation on 125-N Series Insulated Buses.
Connection	Compression
Material	Aluminum
Finish	Tin Plated
Insulation	None

### Dimensions and Classifications

Brand Name	Homac
Standard	ANSI C119.4
Size	Pad Length 3 inch, width 1-1/4 inch
Wire Size	336.4 to 400 kcmil , 500 kcmil , 336.4(18/1) ACSR AWG , 397.5(18/1) ACSR AWG

  
by ABB  
[electrification.us.abb.com](https://electrification.us.abb.com)

Created On: 09/09/2024