



Representative

**Catalog Number:** SAL 650 NTN  
**Product ID:** 7TAA262020R0228  
**UPC Number:** 78378674863  
**Status:** A

Tin-Plated Aluminum Compression Lug for Aluminum and Copper Terminations, Two-Hole NEMA Pad, Wire Range 556.5(24/7, 26/7) ACSR, 600-363-650 kcmil Stranded AL-CU, 556.5 AAC, 750 Compact. Installing dies 140H, 301, 342, 724, 1 1/2, 39ART. Length 8-9/16 inch. Pad 1-19/32 inch wide x 3-21/32 inch long x 9/16 inch thick, (2) 9/16 inch diameter holes on 1-3/4 inch center, uses 1/2 inch Bolt. Barrel 3-19/32 inch. Oxide Inhibitor. Clear Cap.

- Entire Conductor Range Installed by Three Common Dies to Reduce Your Die Inventory.
- Dual-Rated for Use with Aluminum and Copper Conductors.
- Made of Aluminum for High Strength and High Conductivity.
- Prefilled with Oxide Inhibitor to Prevent Oxidation and Keep Out Moisture.
- All Lugs Marked with Conductor Size and Die References for Easy Identification.

**North American Specifications (UNSPSC)**

UNSPSC	39121409 Wire connectors
IGCC	4543 Wire connectors
Type	Compression Lug Two Hole
Special Features	Marked with Conductor Sizes and Die References. Oxide Inhibiting Compound, Clear Cap.
Size	Length 8.562 inches, Pad Width 1.750 inch
Connection	Compression
Wire Size	600 to 640 kcmil ; AAC 556.5 kcmil ; 750 kcmil
Material	Aluminum
Finish	Tin Plated
Insulation	None
Mounting	Bolt Size 1/2 in

**Packaging**

Outer Quantity	25
Outer Dimensions (inches)	1x1x1
Weight Uom	1.03 lbs. Each

**Documents / Support Tools**

Safety Data Sheet (SDS) Global	SDS-00041-TB2
--------------------------------	---------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com