Specifications





Eaton Cooper Power series EZ II Splice, 25 kV, AC 1 min: 52 kV, DC 15 min: 100 kV, BIL: 150 kV, Cable insul: 0.89-1.140 inch, Strand A: 1/0 AWG, Solid A: 2/0 AWG, Al splice, Bulk pack 25

General specifications	
PRODUCT NAME	Eaton Cooper Power series EZ II Splice
CATALOG NUMBER	SP25C004
UPC	194006026154
PRODUCT HEIGHT	9.5 in
PRODUCT DIAMETER	2 in
PRODUCT WEIGHT	0.7 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 404





Accessories	
WITH TEST POINT	No

Additional Specifications	
PACKAGING	Bulk pack 25
ТҮРЕ	EZ II Splice

Cable dimensions	
CABLE INSULATION DIAMETER - MAX	1.14 in
CABLE INSULATION DIAMETER - MIN	0.89 in

Conductor	
CONDUCTOR A SOLID OR COMPACT	2/0 AWG
CONDUCTOR A STRANDED OR COMPRESSED	1/0 AWG
CONNECTOR TYPE	Aluminum splice

Electrical Ratings	
AC 1 MINUTE VOLTAGE WITHSTAND	52 kV
BASIC IMPULSE LEVEL	150 kV
DC 15 MINUTE WITHSTAND	100 kV
MAXIMUM RATING PHASE-TO-GROUND	14.4 kV
CORONA VOLTAGE LEVEL - MIN	22 kV
VOLTAGE RATING	25 kV

Resources	
CATALOGS	One-piece EZ II splice
INSTALLATION INSTRUCTIONS	15 kV and 25 kV class EZ TM II splice installation instructions (For A, B, and C cable ranges only)
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - SP25C004 Line installation and protective equipment specifiers guide

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







