

NOTES

- 1. POLE TESTED AS PER ASTM F711 AND IEC 60855.
- 2. TOOL TESTED AS PER ASTM F1826 AND IEC 62193.
- 3. USABLE LENGTHS 7 ft.
- 4. RETRACTED LENGTH: 28 in. EXTENDED LENGTH: 7 ft.
- 5. BASE DIAMETER 1 7/8" TIP DIAMETER 1 1/16".
- 6. WEIGHT 2 3/4 lb.
- 7. BUTTON REPAIR KIT: T4031248.
- 8. STORAGE BAG: C4032813.

5 A	S.NO.	PART N
(15) x 2	1	P403
	2	P403
(7)(13)(11)	3	P403
	4	P403
	5	P403
	6	P403
(2)	7	P403
	8	P403
	9	P403
$(16)(13)(11)(8)(15)\times 2(4)$	10	P403
	11	P403
	12	P403
	13	P403
	14	P403
(3)	15	P001
	16	P403
	17	P403
$\begin{array}{c} 1 \\ \end{array}$	18	P001
	19	M44
	20	P403
B 16 14 12 10		

S.NO.	PART NUMBER	DESCRIPTION	QTY.
1	P4033425P	BASE TUBE 1.87"OD x22.88"	1
2	P4033428P	TUBE 1.27"OD x 17.69"	1
3	P4033427P	TUBE 1.47"OD x 19.43"	1
4	P4033426P	TUBE 1.67"OD x 21.19"	1
5	P4033429P	POLE 1.07"OD x 17.06"	1
6	P4031011P	BOTTOM CAP, DIA 1.76"	1
7	P4031007P	PLUG, DIA 0.90"	1
8	P4031006P	PLUG, DIA 1.16"	1
9	P4031005P	PLUG, DIA 1.36"	1
10	P4031004P	PLUG, DIA 1.56"	1
11	P4033002P	BUTTON	3
12	P4033001P	BUTTON	1
13	P4032351P	SPRING, 1.25 LONG	2
14	P4032352P	SPRING 2.00 LONG	2
15	P0010419P	PIN, .187 DIA X .375 LG	10
16	P4031977P	SPRING RETAINER	3
17	P4030467P	THUMBSCREW	1
18	P0010309P	SELF TAPPING SCR, #8-32 STN STL	7
19	M44559	UNIVERSAL DISCONNECT HD	1
20	P4032514P	UNIVERSAL POLE HEAD	1

CHANCE®

CONFIDENTIAL: THIS DRAWING AND ITS
CONFIDENTIAL: THIS DRAWING AND ITS
CONFIDENTIAL: THIS DRAWING AND ITS
CONFIDENTIAL: THIS DRAWING AND THE
CONFIDENTIAL: THIS DRAWING AND THE
CONFIDENTIAL: AND THE
SOURCE SOUTH AND THE
THE THIS DRAWING AND THE
CONFIDENTIAL: AND THE
THE THIS DRAWING AND THE
CONFIDENTIAL: THIS DRAWING AND T

ISOMETRIC VIEW