

HUBBELL

Power Systems

Tee, Bronze Bolted

By ANDERSON

Catalog # [TCC4050025](#)



Bronze alloy tee for connecting copper cable main to copper cable tap. Clamping bolts have hex-stops for one-wrench installation. All sizes furnished with reversible cable caps. Material: Castings - bronze alloy, hardware - silicon bronze or stainless steel.

Features

- Tee, Bronze Bolted, Cable to Cable, 0.325-0.813 Main to 0.204-0.575 Tap
- Bronze alloy tee for connecting copper cable main to copper cable tap. Clamping bolts have hex-stops for one-wrench installation. All sizes furnished with reversible cable caps. Material: Castings - bronze alloy, hardware - silicon bronze or stainless steel

General

Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug	0
Holes	
Type	Tee, Bolted
UPC	096359330875

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	1.568 lb

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Diameter (Main) - Maximum	0.813 in
Conductor Diameter (Main) - Minimum	0.325 in
Conductor Diameter (Main) Range	0.325 - 0.813
Conductor Diameter (Tap) - Maximum	0.575 in
Conductor Diameter (Tap) - Minimum	0.204 in
Conductor Diameter - Maximum	0.813 in
Conductor Diameter - Minimum	0.325 in
Conductor Diameter Range	0.325 - 0.813
Conductor Type	Copper

Logistics

Pallet Quantity	756
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Video - Hubbell Power Systems 3D Portal to help with](#)

[developing 3D models of substation connector products](#)

[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-TCC4050025-SPEC-EN | REV 6/2024