


Bronze Bolted Tap Lug Terminal

By ANDERSON
Catalog # [TLS89LTP](#)



Bronze alloy terminal for connecting a copper cable directly to a flat copper pad. Recommended for power or grounding applications. Material: Castings-Bronze alloy, Eyebolt-High strength bronze, Hardware-Stainless steel; For copper cable connection to aluminum bus bar, specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number.

Features

- "Recommended for power or grounding applications
- Tin plating will be supplied"

General

Catalog Number	TLS89LTP
EU RoHS Indicator	No
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug	0
Holes	
Type	Tap Lug
UPC	096359331926

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length	1.75 in
Length - Coupling	0 in
Length Before Compression	0 in
Thickness - Mounting Pad	0.75 in
Maximum	
Weight	0.843 lb

Width4.375 in

Electrical Ratings

Maximum Current Rating Amps0
Continuous

Conductor Related

Conductor Diameter - Maximum	1.152 in
Conductor Diameter - Minimum	0.365 in
Conductor Diameter Range	0.365 - 1.152
Conductor Type	Copper

Certifications And Compliance

Buy American CompliantContact Manufacturer

Product Assets

- [Catalogs - Substation Connectors \(SA\)](#)
- [Sales Drawings - C-2618 \(TLD and TLS Product Families\)](#)
- [Sales Drawings - TLS Product Family](#)
- [Specifications - TLS89LTP](#)
- [Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
- [Video - Hubbell Power Systems Quick Ship](#)