



109 Independence Way  
Coatesville, PA 19320  
P: 610-857-2655  
F: 610-857-2986  
graphics@uticom.net  
www.uticom.net

Part # U7010WWN-G-ES-11  
U7000 Reflective Material  
Exterior Pad Mount Label

© Uticom Systems Inc. 2014  
Proprietary and confidential information contained in this drawing is property of Uticom Systems Inc. and is only intended to be viewed by the end user or authorized distributor. Any reproduction in part or as a whole is strictly prohibited unless approved in writing by Uticom Systems, Inc.

Please review this drawing for accuracy. Approved by: \_\_\_\_\_ Date: \_\_\_\_\_

black on orange background

10"

white on blue background

<p>.38" </p> <p><b>WARNING</b></p> <p>.66" Hazardous voltage inside.</p> <p>.38" <b>KEEP OUT!</b> </p> <p>.149" Can shock, burn or cause death.</p> <p>If found damaged or unlocked call your local utility company.</p> <p>.15" </p> <p><b>WARNING</b></p> <p>.2" Underground power cables are located in this area.</p> <p>Before digging call 811.</p> <p>.108" Can shock, burn or cause death.</p> <p></p>	<p><b>NOTICE</b></p> <p>We need room to work safely on this device. Please keep shrubs and structures 10 feet away from the side with doors and 5 feet from other sides. Obstructions may be damaged or removed during service restoration or maintenance.</p> <p><b>AVISO</b></p> <p>Necesitamos espacio suficiente para trabajar sin riesgos en este aparato. Por favor mantenga arbustos y estructuras a 10 pies de las puertas y 5 pies de los lados.</p> <p>Obstáculos podrán ser dañados o removidos durante restauración de electricidad o mantenimiento.</p> <p>▲ USI U7010WWN-G-ES-11 (MM/YY)</p>	<p></p> <p><b>ADVERTENCIA</b></p> <p>.625"</p> <p>Voltaje peligroso adentro.</p> <p><b>¡NO ENTRAR!</b> </p> <p>Puede producir choques eléctricos, quemaduras, o causará la muerte. Si esta dañado o abierto llame a su compañía local de servicios.</p> <p><b>ADVERTENCIA</b></p> <p>Cables subterráneos de voltaje peligroso existen en esta area.</p> <p>Antes de excavar llame al 811.</p> <p>Puede electrocutar, quemar, o causar la muerte.</p> <p></p>
--	--	--

7"

1/4" round corners

All other graphics print black on white.

**U7000 Material:** 0.007" retro-reflective sheeting, road sign grade with enclosed optical lens elements, engineering grade. Printed using automotive grade solvent based ink, thickness dry .0004" +/- .0001" with 30 micron emulsion, applied using a 158 mesh screen. Short term UV cured inks are not acceptable. **Over laminate:** 0.002" UV filtering PVDF over laminate. **Adhesive:** 0.0015" solvent based, permanent acrylic ASTM grade D 4956 Class 1 with .007" protective liner, kraft coated one side, with back slit. After 72 hours non removable intact. Water based adhesives or film liners are not acceptable in any part of this construction.

**Durability:** Minimum lifetime exterior durability of 20-25 years with proper surface preparation. Defective materials will be replaced at no charge. All parts shall be date stamped with month and year of manufacture.

**Compliance:** NESC and ANSI Z535-2011 compliant, UL 969 certified. All pieces shall pass a UL 969 Legibility Test and UL 969 Defacement Test. Material must have a current UL file number to be approved. Uticom UL file number for U7000 material is MH48956. Uticom will monitor all applicable standards and update graphics as changes occur.

**Installation:** Minimum safe viewing distance is 4.5 feet per ANSI Z535.2-2011 Table B1.