

## KUP-L-TAP® UPC INSULATION PIERCING



- Body is molded from tough, resilient glass-filled nylon to provide a high degree of breakage resistance and long dependable use
- UL Listed and CSA Certified
- Ensures reliability for copper or aluminum conductors
- Compact design saving space
- Tin plated copper contact teeth to easily penetrate most types of insulation
- Insulation piercing - no need to strip the conductor which saves installation time
- Perforated end tabs which break out easily by hand
- Pre-filled with silicone lubricant - prevents oxidation and moisture from entering the contact area
- Can be used as a splice or tap connector
- Contains no external energized parts. Can be installed 'hot' or energized conductors providing tap conductor is not under load
- Horizontal line grid providing a visual guide for proper installation of conductors
- Temperature rating of 90&#176; C
- Meets or exceeds ANSI C119.5
- UPC-4/0-14 is for metering only.
- UPC-4/0-2/0, UPC-250-4/0 and UPC-500-500 may also be used on bare conductor

Item ID	Figure Number	Conductor Range Main	Conductor Range Tap	Voltage	Ampere Rating CU	Ampere Rating AL	Length	Width	Height	Recommended Torque	Bolt Head Size	Standard Package	NAED/UPC Number
UPC-4/0-6	2	4/0-4	6-14	600	75	60	1.4219	1.0000	1.8750	13	1/2	12	0676566790 992