

SKU: UPTF4-500

UPC: 0676566853178

Features & Benefits:

Description: Aluminum Universal In-line Padmount Transformer Bar, Dual Rated, Conductor Range 500-6, 4 Ports



Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	4
Number of Ports Tap	0

Additional Technical Specifications

Conductor Type	Stranded
End Hole Style	Slip-fit

Dimensions

Drive Size Main	5/16
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	NA
Height (IN)	0
Height BX (IN)	7
Length (IN)	0
Weight (LB)	0
Weight BX (LB)	0
Width (IN)	0
Width BX (IN)	8

Material and Finish

Conductor Material	Copper
Connector Finish	Clear
Insulation	NA
Locking Screw Finish	Tin
Locking Screw Material	Aluminum
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	No

Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	67656685317

Environment and Temperature

Water tight	No
-------------	----

Testing Standards

ANSI Specification	ANSI C119.6 Class A
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Bolt and Screw Sizes

Locking Screw Drive Size	5/16
Locking Screw Drive Type	Internal Hex
Transformer Stud Size	5/8-11
Wire Binding Screw Size	3/4-16

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Street Light Tap	No