



SKU: UPTF4-500C

UPC: 0676566852799

Features & Benefits:

Description: Aluminum Universal In-line Padmount Transformer Bar, Dual Rated, Conductor Range 500-6, 4 Ports, Includes Clear Slip On Cover

Specs

Additional Class Attributes

| | |
|----------------------|------------|
| Connection | Mechanical |
| Contains DE-OX® | No |
| Number of Conductors | 4 |
| Number of Ports Tap | 0 |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
| End Hole Style | Slip-fit |

Dimensions

| | |
|-----------------|--------------|
| Drive Size Main | 5/16 |
| Drive Size Tap | NA |
| Drive Type Main | Internal Hex |
| Drive Type Tap | NA |
| Height (IN) | 0 |
| Height BX (IN) | 7 |
| Length (IN) | 0 |
| Weight (LB) | 0 |
| Weight BX (LB) | 0 |
| Width (IN) | 0 |
| Width BX (IN) | 8 |

Material and Finish

| | |
|--------------------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish | Clear |
| Locking Screw Finish | Tin |
| Locking Screw Material | Aluminum |
| Material | Aluminum |
| Wire Binding Hardware Finish | Tin |
| Wire Binding Hardware Material | Aluminum |

General

| | |
|-----------------------------|----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 6 |
| Direct Burial | No |
| Dual Rated | Yes |



NEMA Code

S-569-1

UPC Code

67656685279

Environment and Temperature

Water tight

No

Testing Standards

ANSI Specification

ANSI C119.6 Class A

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

NA

UL File Number

NA

Bolt and Screw Sizes

Locking Screw Drive Size

5/16

Locking Screw Drive Type

Internal Hex

Transformer Stud Size

1-14

Wire Binding Screw Size

3/4-16

Color

Color

Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

500 kcmil - 6 Str

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

500 kcmil - 6 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Street Light Tap

No