



SKU: UPTF4-500CSLP

UPC: 0676566852829

Features & Benefits:

Description: Aluminum Universal In-line Padmount Transformer Bar, Dual Rated, Conductor Range 500-6, 4 Ports, Street Light Tap, With De-Ox, Includes Clear Slip On Cover



Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	5
Number of Ports Tap	1

Additional Technical Specifications

Conductor Type	Stranded
End Hole Style	Slip-fit

Dimensions

Drive Size Main	5/16
Drive Size Tap	5/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	0
Height BX (IN)	6.75
Length (IN)	0
Weight (LB)	1.0612
Weight BX (LB)	6.9674
Width (IN)	0
Width BX (IN)	13.5

Material and Finish

Conductor Material	Aluminum
Connector Finish	Clear
Locking Screw Finish	Tin
Locking Screw Material	Aluminum
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	Yes



NEMA Code

S-569-1

UPC Code

67656685282

Environment and Temperature

Water tight

No

Testing Standards

ANSI Specification

ANSI C119.6 Class A

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

NA

UL File Number

NA

Bolt and Screw Sizes

Locking Screw Drive Size

5/16

Locking Screw Drive Type

Internal Hex

Transformer Stud Size

1-14

Wire Binding Screw Size

3/4-16

Color

Color

Clear

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

500 kcmil - 6 Str

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

500 kcmil - 6 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Street Light Tap

Yes