



SKU: USPA-500SSP

UPC: 0676566793870

Features & Benefits:

Description: Watertight Underground In-Line Splice, Dual Rated, Direct Bury, Conductor Range 500-2, With De-Ox

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Ports Tap	1

Dimensions

Drive Size Main	5/16
Drive Size Tap	5/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	3.899
Height BX (IN)	6.75
Height (mm)	99.0346
Length (IN)	10.745
Length (mm)	272.923
Weight (LB)	1.33965736215585
Weight BX (LB)	16.0439
Width (IN)	1.899
Width BX (IN)	13.5
Width (mm)	48.2346

Additional Technical Specifications

Conductor Type	Stranded
Dielectric Strength	240 V/Mil

Material and Finish

Conductor Material	Copper
Insulation	EPDM
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	Yes

Dual Rated	Yes
NEMA Code	S-569-2
UPC Code	67656679387

Environment and Temperature

Water tight	Yes
-------------	-----

Testing Standards

ANSI Specification	ANSI C119.4 Class A
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Bolt and Screw Sizes

Disc Pad Screws	No
Wire Binding Screw Size	15/16-16

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA