

Aluminum Compression Terminal
for 700 - 750 AL, 556.5 30/7, 636
18/1, 605 24/7, 26/7, 715.5 36/1,
750 - 800 COMPACT

By ANDERSON
Catalog # [VAUL75012BN](#)



*Representative Image

Aluminum Compression Terminal for 700 - 750 AL, 556.5 30/7,
636 18/1, 605 24/7, 26/7, 715.5 36/1, 750 - 800 COMPACT

Features

Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

General

Catalog Number	VAUL75012BN
Color Code	None
Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	2
Physical Attribute - Number of Holes	2
Plating	No
Style	Impact Extruded
UPC	096359334972

Dimensions

Diameter - Pad Bolt	0.5 in
Dimension - Hole Size inch	0.500 in
Dimensions	6.870 in x 1.370 in x 0.560 in
Height	0.56 in
Length	6.87 in
Weight	0.503 lb
Width	1.37 in

Conductor Related

Conductor Compatibility	ACSR-Lark-397.5-30/7;ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Hen-477-
-------------------------	---

30/7;ACSR-Osprey-556.5-18/1;ACSR-Parakeet-556.5-24/7;ACSR-Dove-556.5-26/7;ACSR-Eagle-556.5-30/7;ACSR-Peacock-605-24/7;ACSR-Squab-605-26/7;ACSR-Teal-605-30/19;ACSR-Kingbird-636-18/1;ACSR-Swift-636-36/1;ACSR-Rook-636-24/7;ACSR-Grosbeak-636-26/7;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAC-Meadowsweet-600-37;AAC-Orchid-636-37;AAC-Flag-700-61;AAC-Violet-715.5-37;AAC-Nasturtium-715.5-61;AAC-Cattail-750-61;ACAR-653.1-12/7;ACAR-739.8-18/19

Conductor Diameter (VersaCrimp) - Maximum	0.988 in
Conductor Diameter (VersaCrimp) - Minimum	0.806 in

Certifications And Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	40
-----------------	----

Product Assets

[Catalogs - Distribution Connectors](#)
[Installation Manuals - VAUL Terminals Installation Procedures](#)
[Sales Drawings - VAULxxx_drawing](#)
[Specifications - VAUL75012BN](#)