

556 - 636 MCM Compression Splice
VERSA-CRIMP®

By ANDERSON
Catalog # [VCJS832R](#)



*Representative Image

Features

- For use with VC8 tools only
- Partial tension (40% tension rating) jumping splice
- Can be used with compressed (compact) conductor sizes within the same decimal range

General

Catalog Number	VCJS832R
Compression Method	VersaCrimp Tooling ONLY VC8
Compression Tool Type	VersaCrimp Tooling ONLY VC8
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum Alloy
UPC	096359336778

Dimensions

Length Before Compression	12.88 in
Weight	1.274 lb

Conductor Related

Conductor Compatibility	ACSR-Hawk-477-26/7;ACSR-Hen-477-30/7;ACSR-Osprey-556.5-18/1;ACSR-Parakeet-556.5-24/7;ACSR-Dove-556.5-26/7;ACSR-Kingbird-636-18/1;ACSR-Swift-636-36/1;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAC-Meadowsweet-600-37;AAC-Orchid-636-37;ACAR-653.1-12/7
Conductor Diameter (VersaCrimp) - Maximum	0.94 in
Conductor Diameter (VersaCrimp) - Minimum	0.856 in

Certifications And Compliance

UL Listed	No
-----------	----

Product Assets

- [Catalogs - Distribution Connectors](#)
[Sales Drawings - VCJS_drawing](#)
[Specifications - VCJS832R](#)