





WATCH LIGHT Series

WLT LED Security Lighting



PRODUCT OVERVIEW





DIMENSIONS



R3/R5 Optic



D3/D5 Optic



N3/N5 Optic

Effective Projected Area (EPA). The EPA for the WLT is 0.35 sq. ft, Weight= 7.5 lbs. (3.4 kg)

STANDARDS

Rated for -40°C to 40°C ambient

CSA Certified to U.S. and Canadian standards

Complies with ANSI: C136.2, C136.10, C136.31, C136.15, C136.37

DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

Features:

OPTICAL

Durable prismatic glass optics

Wide variety of lumen packages in type 3 & 5 distributions

Optional acrylic refactor provides additional vertical foot-candles

3000K & 4000K CCT, 70 CRI minimum

ELECTRICAL

120 – 277 volt

Ships standard with 0-10V dimmable driver, or optional DALI D4i driver

Robust Surge Protection: Three different surge protection options provide a minimum of 6kV/3kA, 10kV/5kA or 20kV/10kA protection, per ANSI C136.2.

Expected Life: LED light engines are rated >100,000 hours at 25°C, L70. Electronic driver has an expected life of 100,000 hours at a 25°C ambient.

Lower Energy: Saves an expected of 40-60% over comparable HID luminaires.

MECHANICAL

All aluminum housing & door

2-bolt mounting with +/- 5° adjustment

Mast arm mount is adjustable for arms from 1-1/4" to 2" (1-5/8" to 2-3/8" O.D.) diameter.

Provides a 3G vibration rating per ANSI C136.31

Optional stainless steel thumbscrew for tool-less entry

ANSI standard wattage label on all units

Rigorous pre-treatment and paint process (GY option) yields a finish that achieves a scribe creepage rating of 10 (per ASTM D1654) after 5000 hours exposure to salt fog chamber (operated per ASTM B117).

CONTROLS

The Acuity designed ANSI 7-pin receptacle is available, which supports traditional locking style photocontrols such as the Extreme long-life solid-state locking style photocontrol - PCLL (20 year rated life).

The DC Connect option is a factory embedded low voltage dusk to dawn photocontrol that increases longevity vs. line voltage controls and also eliminates the need to separately inventory controls.

The Local Connect option provides a simple means to collect luminaire attribute data, asset location information and execute point-to-point on/off/dim commands via secure Bluetooth link using smartphone platforms.

Cell Connect is an embedded network photocontrol with cellular communication. It provides digital switching, precise dimming, and revenue grade metrology. Cell Connect leverage D4i drivers to communicate real-time data to UbiVu, a cloud-based asset management system.

WATCH LIGHT Series

WLT LED Security Lighting

ORDERING INFORMATION

Series		Lumen Package		Voltage		Driver		Optics		Color Temperature	
WLT Watch Light		A 34W, 5,000 Nominal Lumens B 43W, 6,300 Nominal Lumens C 51W, 7,400 Nominal Lumens D 62W, 9,100 Nominal Lumens E 72W, 10,200 Nominal Lumens F 79W, 11,100 Nominal Lumens		MVOLT Multiple Voltage 120V-277VAC		ZT 0-10V dimmable D4I DALI D4i driver for 120-277VAC		R3 Roadway Type 3 R5 Roadway Type 5 N3 Type 3 - zero uplight N5 Type 5 - zero uplight D3 Type 3 with Drop Refractor D5 Type 5 with Drop Refractor		3K 3000K Color Temperature, 70CRI 4K 4000K Color Temperature, 70CRI	
Paint		Surge protection		Miscellaneous		Receptacle Top		Receptacle Bottom		Photo Control	
UA Unfinished Aluminum GY Gray Super Durable paint		6K ³ 6kV/3kA, no supplemental surge device MP 10kV/5kA, Fail ON device 20 20kV/10kA Fail OFF device		TB ² Terminal block IG Insect Guard LTS Light trespass shield TL Tool-less door entry CC ¹ UL/CSA Certified PW# Pre-wire, # indicates wire length in one foot increments from 1' thru 10' (e.g. PW4 = 4' of pre-wire) JP Job Pack (30 per pallet)		P3 3 Pin NEMA Photocontrol Receptacle P7 7 Pin Dimming Capable Photocontrol Receptacle ZRT Zhaga Receptacle top NTR No Top Receptacle		NBR No Receptacle Bottom ZRB Zhaga Receptacle Bottom		SH Shorting Cap PCLL DTL DLL Photocontrol DZP DTL DZP DC Zhaga Photocontrol	
Embedded Controls		Install Packages		Install Package with Embedded Controls		Accessories (Shipped Separately)		Controls Training			
ALCB Local Connect Basic (DTL DELC) ALCF Local Connect Full (DTL DELC) ALCC Local Connect Custom (DTL DELC) Requires RFD DDC DC Connect Photocontrol (DTL DEP) UBC Cell Connect		PKGL24 DTL DLL photocontrol + 24" x 1-1/4" arm PKGZ24 DTL DZP photocontrol + 24" x 1-1/4" arm All packages ship with 5' prewire and mounting hardware		PKGE24 ⁴ Embedded Control + 24" x 1-1/4" arm All packages ship with 5' prewire and mounting hardware		WLTLSU Light Trespass Shield for R3 & R5 Optics WLTLSRN Light Trespass Shield for N3 & N5 Optics WLTLS D Light Trespass Shield for D3 & D5 Optics WLTSS Street side Shield for R3, R5, N3, & N5 Optics WLTNU Zero-uplight Shield WLTREF Drop Refractor		LCTRAIN Local Connect Remote Training; 1 day training provided by Acuity Services Team			

NOTES:

- When selected, the CC (UL/CSA Certified) option includes a 3 position terminal block in luminaire. Selection of TB option is not required in that case.
- TB (Terminal Block) option is not required if CC (UL/CSA Certified) option is also selected.
- Not available with UBC option.
- PKGE24 must have Embedded Control nomenclature specified in catalog number.



AEL Headquarters, One Lithonia Way, Conyers Georgia 30012
 www.americanelectriclighting.com Phone: 1-866-HOLOPHANE
 Email: TechSupport-Lighting@acuitybrands.com

© 2016-2024 Acuity Brands Lighting, Inc. All Rights Reserved. WLT Rev. 11/01/24

Warranty Five-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Please contact your sales representative for the latest product information.

WATCH LIGHT Series

WLT LED Security Lighting

OPTIONS MATRIX

WLT		Driver		Receptacle Top				Receptacle Bottom		Photocontrols			Embedded Controls				
		ZT	D4I	NTR	P3	P7	ZRT	NBR	ZRB	SH	PCLL	DZP	DDC	ALCB	ALCF	ALCC	UBC
Driver	ZT			Y	Y	Y	N	Y	N	Y	Y	N	N	N	N	N	N
	D4I			Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Receptacle Top	NTR	Y	Y					Y	Y	N	N	N	Y	Y	Y	Y	Y
	P3	Y	N					Y	N	Y	Y	N	N	N	N	N	N
	P7	Y	Y					Y	Y	Y	Y	N	Y	Y	Y	Y	N
	ZRT	N	Y					Y	Y	N	N	Y	Y	Y	Y	Y	N
Receptacle Bottom	NBR	Y	Y	Y	Y	Y	Y			Y	Y	Y	Y	Y	Y	Y	Y
	ZRB	N	Y	Y	N	Y	Y			Y	Y	Y	N	N	N	N	Y
Photocontrols	SH	Y	Y	N	Y	Y	N	Y	Y				Y	Y	Y	Y	N
	PCLL	Y	Y	N	Y	Y	N	Y	Y				N	N	N	N	N
	DZP	N	Y	N	N	N	Y	Y	Y				N	N	N	N	N
Embedded Controls	DDC	N	Y	Y	N	Y	Y	Y	N	Y	N	N					
	ALCB	N	Y	Y	N	Y	Y	Y	N	Y	Y	N					
	ALCF	N	Y	Y	N	Y	Y	Y	N	Y	Y	N					
	ALCC	N	Y	Y	N	Y	Y	Y	N	Y	Y	N					
	UBC	N	Y	Y	N	N	N	Y	Y	N	N	N					

Y = Option combination is allowed

N = Option combination is not allowed

D4i Driver Option Defaults					
Setting	Receptacle Top	Receptacle Bottom	Embedded Control	Default Value	Alternate Values
DALI Power Bus	NTR	NBR	none	ON	Off
	NTR	NBR	ALCB / ALCF / ALCC	ON	none
	NTR	NBR	DDC	ON	none
	NTR	ZRB	none	ON	Off
	NTR	NBR	UBC	ON	none
	NTR	ZRB	UBC	ON	none
	P7	NBR	none	OFF	On
	P7	NBR	ALCB / ALCF / ALCC	ON	none
	P7	NBR	DDC	ON	none
	P7	ZRB	none	OFF	On
	ZRT	NBR	none	ON	Off
	ZRT	NBR	ALCB / ALCF / ALCC	ON	none
	ZRT	NBR	DDC	ON	none
	ZRT	ZRB	none	ON	Off
Dimming Type	All	All	Any	LINEAR	Logarithmic
24V AUX	All	All	Any	ON (Not Connected)	none
Scenes Data	All	All	Any	0 (blank)	01-255

*To program different settings, consult factory; RFD is required



AEL Headquarters, One Lithonia Way, Conyers Georgia 30012
 www.americanelectriclighting.com Phone: 1-866-HOLOPHANE
 Email: TechSupport-Lighting@acuitybrands.com

© 2016-2024 Acuity Brands Lighting, Inc. All Rights Reserved. WLT Rev. 11/01/24

Warranty Five-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Please contact your sales representative for the latest product information.

WATCH LIGHT Series

WLT LED Security Lighting

PERFORMANCE PACKAGES

WLT Watch Light Performance

WLT Perf Pkg	Distribution	Input Watts	3000K		4000K		BUG Rating			LDD @ 25°C		
			Lumens	LPW	Lumens	LPW	B	U	G	50k hours	75k hours	100k hours
A	R3	34	4,971	146	5,063	149	2	3	2	0.92	0.89	0.85
	R5		5,142	151	5,237	154	3	2	1			
	N3		4,636	136	4,721	139	2	0	1			
	N5		4,831	142	4,921	144	2	0	1			
	D3		4,853	142	4,943	145	2	3	2			
	D5		4,972	146	5,064	149	2	3	1			
B	R3	43	6,205	144	6,320	147	2	3	2	0.92	0.89	0.85
	R5		6,419	149	6,538	152	3	2	1			
	N3		5,787	134	5,894	137	2	0	1			
	N5		6,031	140	6,143	143	2	0	1			
	D3		6,059	141	6,171	143	2	3	2			
	D5		6,208	144	6,322	147	2	3	1			
C	R3	51	7,254	141	7,388	143	2	3	2	0.92	0.89	0.85
	R5		7,504	146	7,642	148	3	2	1			
	N3		6,765	131	6,890	134	2	0	1			
	N5		7,050	137	7,181	139	2	0	1			
	D3		7,082	137	7,213	140	2	3	2			
	D5		7,256	141	7,390	143	2	3	1			
D	R3	62	8,908	142	9,072	145	2	3	2	0.92	0.89	0.85
	R5		9,214	147	9,384	150	3	2	1			
	N3		8,307	133	8,460	135	2	0	1			
	N5		8,657	138	8,817	141	2	0	1			
	D3		8,697	139	8,857	142	2	3	2			
	D5		8,910	142	9,075	145	2	3	1			
E	R3	72	10,073	138	10,259	141	2	3	2	0.92	0.89	0.85
	R5		10,419	143	10,612	146	3	2	1			
	N3		9,393	129	9,567	131	2	0	1			
	N5		9,790	134	9,971	137	2	0	1			
	D3		9,834	135	10,016	137	2	3	2			
	D5		10,075	138	10,262	141	2	3	1			
F	R3	79	10,942	138	11,145	140	2	3	2	0.92	0.89	0.85
	R5		11,318	142	11,528	145	3	2	1			
	N3		10,204	128	10,393	131	2	0	1			
	N5		10,635	134	10,832	136	2	0	1			
	D3		10,683	134	10,881	137	2	3	2			
	D5		10,945	138	11,148	140	2	3	1			

Performance Package	Watts	Current (A)			
		120V	208V	240V	277V
A	30	0.25	0.14	0.13	0.11
B	40	0.33	0.19	0.17	0.14
C	50	0.42	0.24	0.21	0.18
D	60	0.50	0.29	0.25	0.22
E	70	0.58	0.34	0.29	0.25
F	80	0.67	0.38	0.33	0.29

AMBIENT TEMPERATURE FACTOR						
	A	B	C	D	E	F
0°C	1.04	1.04	1.04	1.03	1.03	1.03
15°C	1.01	1.02	1.02	1.01	1.01	1.01
25°C	1.00	1.00	1.00	1.00	1.00	1.00
35°C	0.98	0.98	0.98	0.99	0.99	0.99
40°C	0.98	0.97	0.97	0.98	0.98	0.98



AEL Headquarters, One Lithonia Way, Conyers Georgia 30012
 www.americanelectriclighting.com Phone: 1-866-HOLOPHANE
 Email: TechSupport-Lighting@acuitybrands.com

© 2016-2024 Acuity Brands Lighting, Inc. All Rights Reserved. WLT Rev. 11/01/24

Warranty Five-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Please contact your sales representative for the latest product information.