



Account Details

Account No.	9036149_USS6_10_10
Account	KENTUCKY ASSOC OF ELEC COOPS
Address	KENTUCKY ASSOC OF ELEC COOPS, 4300 CHAMPIONS TRACE LN, , LOUISVILLE, Kentucky, 40218, United States
Sales Org.	ABB Installation Products USA
Sales	Distribution
Currency	USD
As on Date	12-13-2024

Catalog No. X1N4020

Product Details



UPC: 783786759279

Details: Aluminum 5-1/2 inch Service Entrance Compression Splice for Wire Range, End A: 4/0 ACSR, 4/0 Stranded, Gray, End B: 2/0 ACSR, 2/0 Stranded, 3/0 Stranded Compact, Gray, Die: 840. For AL to AL or AL to CU Conductors.

Product Details

Details

Catalog No.	X1N4020
Description	AL SERV ENTR SPLICE 4/0 4/0 GRY
Std. Package Weight	0.180 LB
Product Family	93C
Restock Fee	
Customer Reference No.	
Brand Name	HOMAC
Minimum Order Qty.	100

UPC	783786759279
GSA Compliance	No
Discount Schedule	93
CCC	
Currency	USD
Notes	No standard price available. Book price displayed
Package Qty.	100
Country of Origin	United States

General Characteristics

Category	Wire or cable compression splice
Type	Compression Splice Service Entrance Insulated
Special Features	Solid center barriers and large chamfers. Easy cable installation. Pre- filled with oxide inhibitor to prevent oxidation and keep out moisture. Constructed from Aluminum. Provides high conductivity. All splices are marked with installation die codes and compression locations for easy identificaton and installation. Tough
RoHS	RoHS3 Compliant
REACH SVHC	REACH 223 Compliant
TSCA	TSCA Section 6(h) Compliant
Connection	Compression
Conductor Range	End A: 4/0 ACSR , 4/0 STR , 4/0 COMPR , 250 kmcil COMPT. End B: 2/0 ACSR , 2/0 STR , 2/0 COMPR , 3/0 COMPT
Number Of Conductors	2
Material	Aluminum
Color	Pink/Gray
Insulation	Insulated

Dimensions and Classifications

Brand Name	Homac
Standard	ANSI C119.4
Size	5-1/2 inches long

