

Suspension Clamp

By ANDERSON
Catalog # [YAAC125](#)



Intended for angle construction with AAC, ACSR, or AAAC conductors. See Catalog Reference section for maximum conductor temperature guidelines. Built-in Y-Clevis Fitting allows compound horizontal and vertical angles necessary for residential and urban construction. material: body and keeper - aluminum alloy, hardware - galvanized steel, cotter pin - stainless steel.

Features

Intended for angle construction with all aluminum, ACSR or aluminum alloy conductor,Built-in Y-Clevis Fitting,Horizontal and vertical angles

General

Bolt Installation Torque (Recommended)	300 in-lbs
Catalog Number	YAAC125
Fitting Type	None
Material - Clamp	Aluminum
Material - Hardware	Galvanized Steel
Product Category	Suspension Clamp
Strength Rating - Ultimate	12000 lb
Body	
Type	Standard Voltage Suspension Clamps
UPC	096359363491

Dimensions

Angle - Take-Off Maximum	45 °
Clamping - Maximum	1.25 in
Clamping - Minimum	0.5 in

Diameter - Bolt	0.75 in
Height	4.27 in
Length	4.83 in
Weight	2 lb

Electrical Ratings

Voltage Application	Standard
---------------------	----------

Conductor Related

Clamping Range	0.5- 1.25
----------------	-----------

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	-----------------------------------------------------

Logistics

Pallet Quantity	360
-----------------	-----

Product Assets

[Catalogs - Transmission Connectors Catalog - Full](#)
[Literature - Ropes Course Industry Letter \(April 2021\)](#)
[Specifications - YAAC125](#)