

YCA30R2N, Al compression lug, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # [YCA30R2N](#)



AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.71 IN L

Features

- Aluminum Compression Terminal
- 2-Hole, 1/2" Stud, 1-3/4" Spacing

Application

Aluminum compression HYLUGs for terminating overhead conductors to switch pads and substation or switch yard apparatus.

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Contact Manufacturer
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Str Size	<ul style="list-style-type: none"> • 266.8 (18/1) Waxwing kcmil • 266.8 (26/7) Owl kcmil • 266.8 (26/7) Partridge kcmil
Conductor - ACSR Str Size Range	266.8 (18/1) Waxwing kcmil-266.8 (26/7) Partridge kcmil
Conductor - AL Str Size	266 kcmil
Conductor - AL Str Size Range	266 kcmil

Configuration

Physical Attribute - Pad Configuration	2 Hole NEMA
Connector Type	Terminal

Dimensions

Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - Outside Diameter inch	1.00 in
Dimension - L Length Overall mm	170 mm
Dimension - Pad Width inch	1.42 in
Dimension - B Length inch	2.57 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - Length Overall inch	6.71 in

General

Die Index	251
Prefilled Oxide Inhibitor	Y
Sub Brand	HYLUG
Plated	N
Construction Material - Main Type	Aluminum YCA-R-2N
UPC 12 Digit	781810810491
UPC 14 Digit GTIN	00781810810491
Material	Aluminum
Plating Type	Unplated
UPC	781810810491

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	5920

Product Assets

[Catalog \[English\]](#)