

# YCA321R2N

by Burndy  
Catalog ID: YCA321R2N

Prop 65 Notice

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.95 IN L.

Features: Aluminum compression HYLUG , NEMA standard mounting holes, Installed with same dies as equivalent full-tension sleeves



## Product Details

### General

Application	Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.
Connector Type	Terminal
Die Index	321
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL
Type	YCA-R-N
UPC	781810810736
UPC 12 Digit	7818108107366

### Dimensions

Dimension - B Length inch	2.68 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	178 mm
Dimension - Length Overall inch	7 in
Dimension - Outside Diameter inch	1.12 in
Dimension - Pad Width inch	1.54 in

### Conductor Related

Conductor - ACSR Str Size	336.4 (18/1) Merlin kcmil
Conductor - ACSR Str Size Range	336.4 (18/1) Merlin kcmil
Conductor - AL Str Size	336 kcmil
Conductor - AL Str Size Range	336.4 -350 Kcmil

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

**For further technical assistance, please contact us**

**BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)