

YCA43R2N

By Burndy
Catalog # [YCA43R2N](#)

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 10.28 IN L.



General

Connector Type	Terminal
Die Index	292;319
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYLUG™
UPC	781810016671
UPC 12 Digit	7818100166711

Dimensions

Dimension - B Length inch	5.30 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	260 mm
Dimension - Length Overall inch	10.28 in
Dimension - Pad Width inch	2.48 in

Conductor Related

Conductor - ACSR Str Size	605 (30-19) kcmil;636 (24-7) kcmil;636 (26-7) kcmil;636 (30-19) kcmil;666.6 (24-7) kcmil
Conductor - ACSR Str Size Range	605 (30-19) kcmil;636 (24-7) kcmil;636 (26-7) kcmil;636 (30-19) kcmil;666.6 (24-7) kcmil
Conductor - AL Str Size	700 kcmil;750 kcmil;795 kcmil
Conductor - AL Str Size Range	700 kcmil;750 kcmil;795 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	6
Minimum Pack Quantity	1
Pallet Quantity	1008

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SD..029515-01](#)