

YCS26RL, Aluminum Sleeve, Staked **Cable Stop**

By Burndy Catalog # YCS26RL

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses, Conductor: 1/0 (ACSR, 6201, 5005, AAC).



General

Catalog Number YCS26RL Connector Type Splice Die Index Material Aluminum

Plated Ν

Plating Type Unplated

Prefilled Oxide Inhibitor

Trade Name UNISPLICE™ UPC. 781810015018 **UPC 14 Digit GTIN** 00781810015018

Dimensions

Dimension - B Length inch 2.7 in Dimension - L Length Overall 141 mm

mm

Dimension - Length Overall 5.56 in

Dimension - Outside Diameter 0.83 in

inch

Conductor Related

Conductor - AAAC 5005 Size 2/0 (7) AWG Conductor - AAAC 5005 Size 2/0 (7) AWG

Range

Conductor - AAAC 6201 Size 2/0 (7) AWG Conductor - AAAC 6201 Size 2/0 (7) AWG

Range

Conductor - ACSR Str Size 2/0 (6/1) Quail AWG Conductor - ACSR Str Size 2/0 (6/1) Quail AWG

Range

Conductor - AL Str Size 2/0 (7) AWG Conductor - AL Str Size Range 2/0 (7) AWG

Certifications And Compliance

Certification - CSA Approved Nο Certification - ETL No Certification - UL Recognized Nο Certification - cULus Standards - RoHS Compliance СМ

Status

UL Listed Nο

Logistics

Carton Quantity 25 Minimum Pack Quantity 9800 Pallet Quantity

Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_YCS25RL_LineArt

Sales Drawings - SD..052277-01

Specifications - YCS26RL

