

YRA1CU1, Aluminum Lug, Prefilled with Oxide Inhibitor

By Burndy
Catalog # YRA1CU1



AL compression lug for joining AL and CU cable to transformer and equipment pads, Prefilled with PENETROX, Outside Dia: .56 IN.

General

Catalog Number	YRA1CU1
Die Index	243;BG
Material	Aluminum
Physical Attribute - Pad Configuration	1 Hole
Physical Attribute - Tongue Type	Standard
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYLUG™
UPC	781810016886
UPC 12 Digit	7818100168866

Dimensions

Dimension - B Length fraction	2-9/16 in
Dimension - B Length inch	0.960 in
Dimension - D inch	1.19 in
Dimension - L Length Overall mm	67 mm
Dimension - Length Overall inch	2.62 in
Dimension - N inch	0.53 in
Dimension - Outside Diameter inch	0.64 in
Dimension - Strip Length inch	1 in
Physical Attribute - Tongue Angle	Straight
Thickness - Pad	0.29 in

Conductor Related

Conductor - ACSR Str Size	2 AWG
Conductor - AL Str Size	1 AWG, 2 AWG
Conductor - AL Str Size Range	1 AWG - 2 AWG
Conductor - Copper Str Size	1 AWG, 2 AWG, 3 AWG
Conductor - Copper Str Size Range	1 AWG - 3 AWG

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	50
Minimum Pack Quantity	1
Pallet Quantity	19600

Product Assets

- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YRA_LineArt](#)
- [Sales Drawings - sd077273-01](#)
- [Specifications - YRA1CU1](#)