

YSD28R2R, Aluminum Sleeve with Solid Center Barrier

By Burndy
Catalog # [YSD28R2R](#)



AL compression sleeve with solid center barrier, Designed for commercial and heavy residential services, Color Code: Pink (Side A), Red (Side B)

Features

- Aluminum Compression Sleeve
- Solid Center Barrier

Specifications

Certification - cULus	No
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Copper Str Size A	4 AWG
Conductor - Copper Str Size B	1 AWG, 2 AWG
Conductor - Copper Str Size B Range	1 AWG-2 AWG
Conductor - ACSR Str Size A	4/0 (6/1) Penquin AWG
Conductor - ACSR Str Size B	<ul style="list-style-type: none"> • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG
Conductor - ACSR Str Size B Range	2 (6/1) Sparrow AWG-2 (7/1) Sparate AWG
Conductor - AL Str Size A	4/0 AWG
Conductor - AL Str Size B	1 AWG, 2 AWG
Conductor - AL Str Size B Range	1 AWG-2 AWG

Dimensions

Dimension - Outside Diameter	.3125 in
Dimension - L Length Overall	102 mm
Dimension - Length Overall	4 in

General

Die Index	<ul style="list-style-type: none"> • 249 • K-840
Trade Name	LINKIT™
Plated	N
Type	Service Entrance, Uninsulated
Prefilled Oxide Inhibitor	Y
UPC 12 Digit	781810146002
UPC 14 Digit GTIN	00781810146002
Material	Aluminum
Plating Type	Unplated
UPC	781810146002
Color Code - Side A	Pink
Color Code - Side B	Red

Logistics

Minimum Pack Quantity	25
Carton Quantity	25
Pallet Quantity	7400

Product Assets

[Catalog \[English\]](#)